

## LUHONG 25HP 4x4 Tractor



1) Model: LZ 254, 25hp, 4x4.

2) Chinese 3 cylinders EPA diesel engine, dual stage clutch, Inner Filter, hydraulic Power steering,  
Tire: 6.0-14(F) 9.5-24(R), Rops, Sunshade.

Options:

- Shuttle Shift
- Front Ballast
- Rear Ballast
- Roll Bar
- Sun-shade
- Swing Draw Bar
- Down Exhaust Pipe
- Multi-way valve
- Creeper
- Air brake
- Turf tire

**Note:** Shuttle shift and creeper not available at the moment.

3) SKD packing with iron crate (For dealers and ex. PDI freight)

4) Warranty: 12 months from invoice date

## 5. Specification

Parameters			
Model		LZ254	
Type		4WD Wheeled Type	
(mm) Dimensions of Tractor	Length (to front ballast)		3030
	Width		1470
	Height (to the exhaust vent)		1900
	Tread	Front Wheel	1215 Fixed or 1150~1215 Adjusted
		Rear Wheel	1300 Fixed or 1300~1350 Adjusted
	Axle Base		1710
	Min. Ground Clearance		347.5
Structure weight (kg)		1130	
Ballast weight (kg)	Front ballast	56	
	Rear ballast	112	
Rated traction force (kg)		551	
Engine	Model		385
	Type		Vertical,3-Cylinder,Water Cooled and 4-stroke
	Rated Power(kw)		18.3
	Rated speed (r/min)		2400
	Fuel		Diesel
Tire	Front Wheel		6.00-14
	Rear Wheel		9.5-24
Clutch		Dual-stage clutch	
Steering		power steering	
Transmission Type		8+2 or 8+8 with shuttle gearshift or 16+4 with creeper shift	
Suspension Type		3-point links	
PTO	Type and Rev		Semi-independent Type 540/1000
	Spline Size		F35 Rectangle Spline with 6 teeth
Structure and specification are subject to change without notice.			

