

# LUHONG 45HP 4x4 Tractor



1) Model: LZ 454,45hp, 4x4.

2) Chinese 4 cylinder EPA diesel engine, dual stage clutch, hydraulic steering, reinforced front axle, Tire: 8.3-20(F) 12.4-28(R), Rops, Sunshade

3) Options:

- Shuttle Shift
- Front Ballast
- Rear Ballast
- Roll Bar
- Sun-shade
- Swing Draw Bar
- Reinforced rear tire 14.9-24
- Multi-way valve
- Creeper
- Luxurious Seat
- Air brake
- Normal Cab
- Cab with heater
- Turf tyre
- External hydraulic and bigger rear axle
- Rear paddy tyre
- 14.9-24 Rear Tyre

Note: Shuttle shift and creeper not available at the moment.

4) SKD packing with iron crate (For dealers and ex. PDI freight)

5) Warranty: 12 months from invoice date

## 6. Specification

Parameters			
Model		LZ454	
Type		2WD Wheeled Type	
(mm) Dimensions of Tractor	Length(With front ballast)		3835
	Width		1620
	Height(to the exhaust vent)		2135
	Tread	Front Wheel	1300 or 1200~1500 Adjusted
		Rear Wheel	1300 Fixed or 1200~1500 Adjusted
	Axle Base		1910
	Min. Ground Clearance		410
(kg) Structure weight		1665	
Ballast weight (kg)	Front ballast	112	
	Rear ballast	100	
Rated traction force (kg)		850	
Engine	Model	495	
	Type	Vertical,4-Cylinder,Water Cooled and 4-stroke	
	Rated Power(kw)	33	
	Rated speed (r/min)	2400	
	Fuel	Diesel	
Tire	Front Wheel	6.00-16	
	Rear Wheel	12.4-28	
Clutch		Dual-stage clutch	
Steering		power steering	
Transmission Type		8+4 or 8+8 with shuttle gearshift or (8+4)×2 with creeper shift	
Suspension Type		3-point links	
PTO	Type and Rev	Semi-independent Type 540/1000	
	Spline Size	F35 Rectangle Spline with 6 teeth	
Structure and specification are subject to change without notice.			

